Docket No.: 08226/1203507-US1

(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Letters Patent of: Janakiram Koka et al.

Patent No.: 7,143,181

Issued: November 28, 2006

For: SYSTEM AND METHOD OF SENDING CHUNKS OF DATA OVER WIRELESS

DEVICES

REQUEST FOR CERTIFICATE OF CORRECTION PURSUANT TO 37 CFR 1.322

Attention: Certificate of Correction Branch

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Dear Sir:

Upon reviewing the above-identified patent, Patentee noted typographical errors which should be corrected. A listing of the errors to be corrected is attached.

The typographical errors marked with an "P" on the attached list are not in the application as filed by applicant. Also given on the attached list are the documents from the file history of the subject patent where the correct data can be found.

The errors now sought to be corrected are inadvertent typographical errors the correction of which does not involve new matter or require reexamination.

Transmitted herewith is a proposed Certificate of Correction effecting such corrections.

Patentee respectfully solicits the granting of the requested Certificate of Correction.

Patent No.: 7,143,181 Docket No.: 08226/1203507-US1

The Commissioner is authorized to charge any deficiency of up to \$300.00 or credit any excess in this fee to Deposit Account No. 04-0100.

Dated: February 23, 2007

Respectfully submitted,

By -

Flynn Barrison Registration No.: 53,970

DARBY & DARBY P.C.

P.O. Box 5257

New York, New York 10150-5257

(212) 527-7700 (212) 527-7701 (Fax)

Attorneys/Agents For Applicant

Approved for use through 04/30/2007. ORB 0661-0033
U.S. Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Papenwork Reduction Act of 1995, no persons are required to respond to a collection of Information unless at displays a valid OMB control number. (Also Form PTO-1050)

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 1 of 1

PATENT NO. : 7,143,181

APPLICATION NO. : 09/938.939

ISSUE DATE : November 28, 2006 INVENTOR(S) : Janakiram Koka et al.

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

First Page Col. 1 (Assignee): Line 1: Delete "Yohoo!" and insert - - Yahoo! - -, therefor.

Column 3; Line 41; Delete "Wireless" and insert - - wireless - -, therefor.

Column 4: Line 37: Delete "aid" and insert - - and - -, therefor.

Column 5; Line 2; Delete "Specific" and insert - - specific - -, therefor.

Column 5; Line 39; Delete "arid" and insert - - and - -, therefor.

Issued Patent Proofing Form Note: P = PTO Error

A = Applicant Error

File#: 08226/1203507-US1

US Serial No.: 09/938,939

US Patent No.: US 7,143,181 B2 Title: SYSTEM AND METHOD OF SENDING CHUNKS OF DATA OVER WIRELESS DEVICES

Issue Dt.: Nov. 28, 2006

Sr. No.	P/A	Original		Issued Patent		Description Of Error	
		Page	Line	Column	Line	·	
1	Р	Page 1 Issue Fee Payment (PTO-85B) (10/23/2006)	1 (Name of Assignee)	First Page Col. 1 (Assignee)	1	Delete "Yohoo!" and insert Yahoo! therefor.	
2	Р	Page 7 Specification (08/24/2001)	6	3	41	Delete "Wireless" and insert wireless, therefor.	
3	Р	Page 9 Specification (08/24/2001)	11	4	37	Delete "aid" and insert and, therefor.	
4	Р	Page 10 Specification (08/24/2001)	14	5	2	Delete "Specific" and insert specific, therefor.	
5	Р	Page 11 Specification (08/24/2001)	23	5	39	Delete "arid" and insert and, therefor.	



(12) United States Patent

Koka et al.

(10) Patent No.: US 7.143.181 B2 (45) Date of Patent: Nov. 28, 2006

(54)		AND METHOD OF SENDING	6,313,854	BI	11/2001	Gibson 345/788
		CHUNKS OF DATA OVER WIRELESS		B1 *	1/2002	Lee et al 709/219
	DEVICES		6,424,828	BI*	7/2002	Collins et al 455/412.1
(75) Inven	Terrostosos	: Janakiram Koka, Palo Alto, CA (US); Sanjeev Dharap, Fremont, CA (US)	6,507,865	BI *	1/2003	Hanson et al 709/206
	mvemors.		6,618,709	BI *	9/2003	Sneeringer 705/412
			6,620,205	B1 *	9/2003	Sequeira 715/513
(73)	Assignee:	Yohoo! Inc., Sunnyvale, CA (US)	6,735,614	BI	5/2004	Payne et al.
(*) No		Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 695 days.	6,763,388	BI*	7/2004	Tsimelzon 709/228
	Notice:		6,834,306	в1*	12/2004	Tsimelzon 709/228
			6,993,559	B1 *	1/2006	Jilk et al 709/206
			2002/0010746	AI*	1/2002	Jilk et al 709/206
(21)	Appl. No.:	09/938,939	2002/0016736	Al*	2/2002	Cannon et al 705/14
			2002/0033844	A1*	3/2002	Levy et al 345/744
(22)	Filed:	Aug. 24, 2001	2002/0059367	Al*	5/2002	Romero et al 709/203
(65)		Prior Publication Data				

(57) ABSTRACT

resource locator, or element boundary.

In a network carrying a web page containing data, a method for dividing the web page into a maximum size chunk. In one aspect, the method comprises determining a chunk size limit, dividing the web page data into segments having a size no greater than said chunk size limit; and linking said chunks in sequence. In particular, the method finds applicability in a wireless network carrying content data via the network through at least one gateway, the gateway having a defined gateway limit. In a further aspect, the method includes: determining where the gateway limit falls in said content data; and parsing the content data into at least a first segment and at least a next segment of a size at or below the gateway

(Continued)

Primary Examiner-Frantz B. Jean (74) Attorney, Agent, or Firm-Darby & Darby PC; Thomas R. Marquis

See application file for complete search history. (56)

31, 2000.

G06F 15/16

(51) Int. Cl.

References Cited U.S. PATENT DOCUMENTS

US 2002/0059459 A1 May 16, 2002

Related U.S. Application Data


(60) Provisional application No. 60/229,721, filed on Aug.

(2006.01)

709/245, 200; 715/500, 51.1, 513; 702/186

5,548,789 A	8/1996	Nakanura 395/853
5.754.778 A	5/1998	Shoujima 395/200.36
5,758,088 A	5/1998	Bezaire et al.
6.021,433 A	2/2000	Payne et al.
6.101.548 A	8/2000	Okada 709/236
6.167.426 A	12/2000	Payne et al.
6.185,585 B1 *	2/2001	Sequeira 715/513
6.185.588 B1	2/2001	Olson-Williams 707/515
6,219,150 B1	4/2001	Eguchi 358/1.15
6,266,684 B1	7/2001	Kraus et al 707/513
6,300,947 B1 *	10/2001	Kanevsky 715/866

limit at break points not falling within a word, universal 20 Claims, 6 Drawing Sheets



quickly occupy the amount of available bandwidth to transmit the document via gateway to user.

STRANGER

An embodiment of the present invention, briefly described, finds application in a network carrying a web page containing data, and provides a method for dividing the web page into a maximum size chunk. In one aspect, the method comprises determining a chunk size limit, dividing 10 the web page data into segments having a size no greater than said chunk size limit; and linking said chunks. In particular, the method finds applicability in a wireless network carrying content data via the network through at least one gateway, the gateway having a defined gateway limit. In 15 a further aspect, the method includes: determining where the gateway limit falls in said content data; and parsing the content data into at least a first segment and at least a next segment of a size at or below the gateway limit at break points not falling within a word, universal resource locator, 20 of accessing a wireless network 15 which is coupled to a or element boundary.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described with respect to the as particular embodiments thereof. Other objects, features, and advantages of the invention will become apparent with reference to the specification and drawings in which:

- FIG. 1 is a block diagram of a wireless device coupling to a wireless network and gateway to the Internet:
- FIG. 2 is an illustration of a full-length web page being divided into smaller portions for transmission via a wireless network, according to an embodiment of the present inven-
- FIG. 3 is a block diagram of a wireless device coupled to as a wireless network including a process server used to implement embodiments of the present invention;
- FIG. 4 is an illustration comparing an original content page, a wireless application protocol page and the amount of information that can be displayed in the display window of 40 40 may have a length which is defined by the allowable data a client device, such as a Wireless telephone, according to an embodiment of the present invention;
- FIG. 5 is a flow chart depicting a first aspect of a method of the present invention:
- method in accordance with the present invention.

DETAILED DESCRIPTION

described, is a system which provides a mechanism for enabling the content of differing sizes and types of web pages, programmed in any number of a standard mark-up languages utilized on web content servers throughout the Internet, to be transmitted via WAP Gateways established by 55 a wireless network of providers. In particular, each such page is divided into a quantity of bytes equaling a maximum length or fewer number of data bytes, in order to allow the page to pass through the gateway.

Illustrated in FIG. 2 is a typical page which may be 60 provided by an Internet content provider. The page may have any number of bytes, but in FIG. 2, page 30 is shown as having approximately 10,000 bytes. Each WAP gateway 20 has a fixed gateway limit of some number, with a typical gateway size being about 1,500 bytes and in one embodi- 65 ment in particular, 1,492 bytes. As such, one solution to allow the typical page 30 to traverse the gateway is to divide

the page into any number of smaller pages 40, 40', 40", etc. An embodiment of the present invention provides a method and system for generating pages 40.40', 40", etc., and inserting a link 50 from the first page to the second page, or any number of sequential pages into which the typical page 30 is broken, dependent upon the gateway limitation imposed by WAP gateway 20.

In accordance with an embodiment of the invention, web page 30 is broken into discrete data chunks, each of which is equal to or less than the size of the gateway limit. In addition, once such breakage has occurred, a link is inserted to each of the discrete pages to transfer to subsequent portions of the chain of data.

The source of the page 30, and a means for implementing various embodiments of the present invention, is illustrated in FIG. 3. FIG. 3 shows a wireless client device 10 which may be a personal digital assistant, wireless cellular phone enabled with a micro browser, or any other device capable wireless gateway 20. Within the public Internet 25, a particular website server 50 is coupled to a WAP server 55 to provide content information to the wireless client 10. In accordance with the invention, the WAP server 55 which is fed content directly from a particular site server 50, includes a series of processes running on the particular format of the server and implemented by any number of known programming methods to implement various embodiments of the present invention. The WAP server 55, in one embodiment, is implemented by a provider or system administrator and implemented for specific content (such as specific web sites) or specific carriers (wireless networks).

FIG. 4 shows how an original page 30 is converted to a more limited page 40 for transmission through a WAP gateway, according to one embodiment of the present invention. In one aspect, page 30 is provided by a content server residing on the public Internet 25, aid is a page normally read by any type of client browser application, such as Netscape's Navigator or Microsoft's Internet Explorer. Page limit of the WAP gateway 20 and is equal to or less than the WAP gateway limit. In page 30, data is consumed by text, meta (or unseen) data, formatting information, and graphics, HDML pages maybe specifically tailored for hand-held FIG. 6 is a flow chart depicting a second aspect of a 45 devices to include only text and icon graphics, but the text of each page 30 is generally longer than the length of the screen display of such devices. As illustrated in FIG. 4 at window 95, seven lines are displayed, but more typically in an Internet-enabled phone, only four lines are available. A An embodiment of the present invention, roughly 50 scroll arrow 97, which is capable of scrolling up and down under the control of the particular client device's available controls (a keypad or other control buttons, dials, etc.), allows a user to view the entire page 40 which is presented in the mini-browser.

> FIG. 5 shows one method, according to an embodiment of the present invention, for reducing a full HTML or HDML web page 30 to a size equal to or less than the allowable data size of the gateway. As discussed with respect to FIG. 3. within the public Internet 25, a website server 50 is coupled to a WAP server 55 to provide content information to the wireless client 10. In accordance with the invention, the WAP server which is fed content directly from a particular site server 50, includes a series of processes running on the particular format of the server and implemented by any number of known programming methods to implement various embodiments of the present invention. The WAP server in this embodiment is implemented by a provider or

system administrator and implemented for specific content (such as specific web sites) or Specific carriers (wireless networks)

As one who is skilled in the art would appreciate, FIGS. 5 and 6 illustrate logic boxes for performing specific func- 5 tions. In alternative embodiments, more or fewer logic boxes may be used. In an embodiment of the present invention, a logic box may represent a software program, a software object, a software function, a software subroutine, a software operation or user operation, singly or in combination.

As shown in FIG. 5, a page input at logic box 100 may be a typical page 30 provided by an Internet content provider which is formatted in HTML, HDML, or any other number of markup languages suitable for processing by a web 15 browser. The method first determines where page breaks occur in text at logic box 102. Logic box 102 is illustrated in further detail in FIG. 6. Once page breaks are determined. at logic box 104, the page breakpoints for each page are each assigned a URL to enable linking to subsequent portions of 20 the page. The URL takes the format [chunkURL] #ADDRESS where the chunkURL is the original URL of the WAP page 85 and the address is the number of the particular chunk 40, 40', 40", etc. in the sequence. At logic box 106, this link is then inserted into each limited page 40, 40", 40" 25 as a hyperlink 50, as shown in FIG. 4, to enable the user to move to the next sequential portion of the page.

Each sequential page 40, 40', 40" is stored on the process server (WAP server 55 or other process server) for display in response to individual requests for each specific portion of 30 the page (40, 40', 40"). At logic box 108, the first portion 40 of page 30 is displayed to the client device 10. When a user selects the "MORE" link 50 in the first page 40, the user will be linked to the second page 40', and the "MORE" link in page 40' will link to page 40", and so on. It should be 35 recognized that while the linking of the URL addresses set forth above is sequential, that is from 40 to 40" to 40" along the length of the page 30, additional links can be provided to jump to different portions in a non-sequential order, arid links may be provided to return to the previous pages.

In one aspect, embodiments of the present invention may be performed prior to other steps in displaying the page. For example, in co-pending application Ser. No. 09/938,799, entitled "REDUCTICN OF METADATA IN A NET-WORK" filed Aug. 24, 2001, inventor Sanjeev Dharap, a 45 process for providing fixed-length string of meta-data, such as a URL, in web pages displayed to multiple devices is provided. In implementation, the embodiment of the present invention may be performed on a server device either prior or subsequent to performance of the methods set forth in 50 chunks is desired. co-pending application Ser. No. 09/938,799. If an embodiment of the present invention is performed prior to conducting the method in co-pending application Ser. No. 09/938, 799, the embodiment of the present invention may assume conversion of all data subject to a method of co-pending 55 by the attached claims. application Ser. No. 09/938,799 will be a fixed length (i.e. each URL will be a fixed-length URL) before calculating break points in pages, as discussed below.

FIG. 6 shows one embodiment of determining break points used in logic box 102 of FIG. 5 for dividing page 30 60 into individualized discrete pages 40,40',40".

The input page 30 is first examined at logic box 110 to determine the location in the text, formatting or other page data where the gateway limit in a page first occurs. As noted above, the gateway limit is determined by counting the 65 number of bytes in the page up to a certain point including all URLs and meta-data (data which is not displayed to a

user during transfer of a page), and the calculation may assume that each of the meta-data or other strings is reduced to a fixed length by the process of co-pending application Ser. No. 09/938,799.

At logic box 112, a determination is made as to whether the gateway limit falls in the middle of the word or other text item. If so, at logic box 114, the algorithm searches for the presence of a format character such as a previous tab, space, or new line indicator, just prior to the point where the word method, a software instance, a code fragment, a hardware 10 occurs. If one of the aforementioned format characters is present, the breakpoint will be inserted at this point in the nage.

> At logic box 116, the method determines whether the gateway limit falls in the middle of a universal resource locator. If so, at logic box 118, the method checks to find the previous tab space, new line or other boundary indicator as a point at which to break the page.

Finally, at logic box 120, the method checks to determine whether an element boundary occurs. Even if a format character is found, if such character is within a table, it would be undesirable to break the page in the middle of a table. If the element boundary does occur, at logic box 122, the method looks for a previous end of form, import element, or end of table. An element boundary may occur in the middle of a table, for example, or form, and it is not desirable to break a page in the middle of a formatted entry. Hence, the boundary start point will be determined and a break point inserted prior to the boundary.

Once logic boxes 112, 116, 120 have been completed, the break point is determined at logic box 128 as the point meeting all the aforementioned conditions.

It should be recognized that the ordering of logic boxes 112, 116, 120 is not exclusive to the embodiment set forth in FIG. 6, and alternative ordering of the logic boxes may occur within the scope of the invention. Next, if the remaining portion of page 30 has a size greater than the gateway limit, additional break points in the document are determined by returning to logic box 110. If not, a link is inserted at logic box 130 into the table (step 104, FIG. 5) and on a subsequent 40 pass at logic box 106, the URLs will be rewritten into the new pages 40, 40', 40"

Embodiments of the present invention provide a mechanism for shortening long web pages into pages which are usable by individuals utilizing limited bandwidth devices such as wireless devices. It will be recognized that the invention has broader applicability beyond wireless devices and can be utilized where any form of gateway eliminating mechanism or any desire to limit bandwidth of particular information transmitted across the network into discrete

The many features and aspects of the present invention will be readily apparent to one of average skill in the art. All such features of the invention are intended to be within the scope of the written description and the drawings as defined

What is claimed is:

1. In a network carrying a web page containing data, a method for dividing the web page into chunks, comprising: determining a chunk size limit;

dividing the web page data into chunks having a size no greater than said chunk size limit; and

linking said chunks in sequence wherein the linking comprises inserting a link in one of the chunks comprising a link to another of the chunks.

2. The method of claim 1 wherein said step of linking, links chunks in a non-sequential manner.